



PROTECTIVE COATINGS



WIWA Herkules GX PFP

Fire and its heat present a great risk to life and property.

Passive fire protection is primarily used to maintain the functionality of buildings, pipelines and containers for a defined period of time, since at temperatures of approx. 550°C the critical core temperature is reached and buildings are at risk of collapse. In the event of a fire, the flame retardant material foams up, thus limiting the temperature development in the respective critical range over time. This saves important time for rescue and evacuation measures.



ADVANTAGES

- Single feed unit for the use for smaller areas and for repairs
- State-of-the-art technology
Made in Germany
- Highly qualified employees, agents and distributors world- wide for local sales and service
- Competent customer service in the local language
- Safe and easy system operation
- Top quality and service at a fair price

AREAS OF APPLICATION

- Fire protection
- Corrosion protection
- Marine industry
- Steel construction
- Industry

Technical Data	
Output per cycle (cm ³)	275
Pressure ratio	75:1
Max. output at 60 double strokes (l/min)	16,5
Max. operating pressure (bar/psi)	450/6526
Order No.	0663691
Order No. Accessory kit PFP ready-for-spraying version	0651003
Order No. Version ATEX Zone 1	0659712
Order No. Accessory kit PFP ready-for-spraying version ATEX	0659712



Maintenance unit



Follow-up lid



Control unit

• For smaller areas and for repairs

• Supply of spare parts and accessories readily available


• Commissioning and training at customers location or job site



 WIWA Wilhelm Wagner GmbH & Co. KG

 WIWA Wilhelm Wagner GmbH & Co. KG

 @wiwa_airless_global_hq

 +49 (0) 6441 609-0

 sales@wiwa.de

Head Office and Production Germany
WIWA Wilhelm Wagner GmbH & Co. KG
Gewerbestraße 1-3
35633 Lahnau
Telefon: +49 (0) 64 41 / 6 09-0
www.wiwa.de

WIWA Subsidiary USA
WIWA LLC – USA, Canada, Latin America
107 N. Main St., Alger, OH 45812
Phone: +1-419-757-0141
Toll-Free: +1-855-757-0141
www.wiwausa.com

