CI/SfB		November 2017		
		Ln6	B2d	
Uniclass	Pr_25_	71_29_7	76	
			lssue 01 Rev 0	



Monarflex[®] Scaffband Clear

TECHNICAL DATA SHEET

Upper Layer	Coated Co-polymer LDPE
Type of Reinforcement	9 mm x 12 mm 1670 dtex PET grid
Lower Layer	Blown Co-polymer LDPE
Eyelet /Structural Type	70 mm wide woven HDPE reinforcement tapes
Colour	Clear

Test method	Value or statement	Tolerance	Units
EN 1848-2	36; 45	36; 45 ±1 %	
EN 1848-2	2.0; 2.25; 3.0 -0.5 / +1.5 %		m
EN 1849-2	0.115	±5 %	mm
EN 1849-2	158	-5 / +10 %	g∙m-2
EN 1928 (B)	Class W1	Class W1 -	
EN 13501-1	Class F	-	-
EN 12311-2	>630	530 -	
EN 12311-2	>630	-	N/50mm
BS 7955	≥ 500 -		N
BS7955, Annex A	Conforms -		-
BS7955, Annex B	Conforms -		-
Monarflex Int. Test	>70	±10	%
	EN 1848-2 EN 1848-2 EN 1849-2 EN 1849-2 EN 1928 (B) EN 13501-1 EN 12311-2 EN 12311-2 EN 12311-2 BS 7955, Annex A BS7955, Annex B	EN 1848-2 36; 45 EN 1848-2 2.0; 2.25; 3.0 EN 1849-2 0.115 EN 1849-2 158 EN 1849-2 158 EN 1928 (B) Class W1 EN 13501-1 Class F EN 12311-2 >630 EN 12311-2 >630 BS 7955 ≥ 500 BS7955, Annex A Conforms BS7955, Annex B Conforms	EN 1848-2 36; 45 ±1% EN 1848-2 2.0; 2.25; 3.0 -0.5 / ±1.5 % EN 1849-2 0.115 ±5 % EN 1849-2 158 -5 / ±10 % EN 1849-2 158 -5 / ±10 % EN 1928 (B) Class W1 - EN 13501-1 Class F - EN 12311-2 >630 - EN 12311-2 >630 - BS 7955 ≥ 500 - BS7955, Annex A Conforms - BS7955, Annex B Conforms -

Roll Size	Roll Area	Reinforced Bands	Sheet Mass per Unit Area	(Gross) Roll Weight
2.0 m x 45 m	90 m ²	3	177 g·m⁻²	17 kg
2.25 m x 40 m	90 m ²	3	175 g·m⁻²	17 kg
3.0 m x 45 m	135 m ²	5	179 g·m⁻²	25 kg

Description of Product

Monarflex Scaffband Clear is a three-layer weather barrier consisting a polyester reinforcing grid with films of special highly weather resistant copolymer low density polyethylene (LDPE) laminated on both sides to form a monolithic membrane. Additional reinforced bands to the edges and centre of the sheet strengthen the fixing eyelet positions.

Type of Application

Monarflex Scaffband Clear is intended for use as a high-performance scaffold protection sheet and is suitable for normal weather conditions on low rise short-term projects with durations of up to 6 months.

Compatibility

The material is compatible with all materials normally used in its application. There are no harmful side effects associated with this material.

Storage and Delivery

Rolls are delivered on pallets, individually wrapped with PE film. These materials should, when removed from pallets, be stored on side, under cover and on a flat, level surface, and protected from mechanical damage and heat sources. During storage exposure to direct sunlight is to be avoided.

Glossary of Terms

"Membrane" comprises the film and reinforcing grid laminate. "Sheet" comprises the membrane including eyelets/reinforcing bands. "Gross roll weight" is scaffold sheet plus packaging and cardboard core.

Factory Ref: S0001-01-101

NOTE: This information is given in good faith being based on the latest knowledge known to lcopal Limited. Whilst every effort has been made to ensure the contents of the publication are current while going to press, customers are advised that products, techniques and Codes of Practice are under constant review and liable to change without notice.